



Date Sep. 9, 2008

No. SBT-02147

Messrs. _____

SPECIFICATION

FOR

3.3KV EP RUBBER INSULATED AND POLYCHLOROPRENE
SHEATHED FLAT TYPE FLEXIBLE CABLE
(F-3PNCT)

Prepared by Y.OI
Y. OI
Senior Design Engineer
Design & Engineering Group
Engineering Department
Industrial & Telecommunication Cable Division

Approved by R.TONEGAWA
R. Tonegawa
Group Manager
Design & Engineering Group
Engineering Department
Industrial & Telecommunication Cable Division

Fujikura Ltd.

CONSTRUCTION DATA

Type of cable		F-3PNCT	
Rated voltage (kV)		3.3	
Number of core		3 (Power)	1 (Earth)
Conductor TA	Nominal sectional area (mm ²)	325	100
	No. and dia. of wire (No./mm)	37/55/0.45	19/34/0.45
	Approx. dia. of conductor (mm)	27.0	15.2
Thick. of semi-conductive layer (mm)		—	—
Thick. of insulation (mm)		4.0	2.1
Approx. thick. of semi-conductive tape (mm)		0.4	—
Flexible copper-fibrous yarn braid Copper (Fibrous yarn)		7/0.26 (Yarn)	— —
Approx. thick. of reinforcement (mm)		0.5	0.5
Colour code		Red, White, Blue	Green
Thick. of sheath (mm)		8.2	
Overall dimension (Height x Width)	Standard (mm)	51.7 X 143.7	
	Maximum (mm)	54.3 X 150.9	
Approx. net weight (kg/km)		17150	
Testing voltage (V/min.)		9000/10	3000/1
Max. conductor resistance at 20°C (Ω/km)		0.0614	0.193
Min. insulation resistance at 20°C (MΩ-km)		200	200

TA : Tinned annealed copper wire

