


DATE Jan. 7, 2015NO. SBT-05440Messrs.

# SPECIFICATION

FOR0.6/1kV EP RUBBER INSULATED AND POLYCHLOROPRENESHEATHED FLAT TYPE FLEXIBLE CABLE(F-3PNCT-S)Project :

**Prepared by** O. Saito  
Senior Design Engineer  
Engineering Department  
Power & Telecommunication Cable Division  
Power & Telecommunication System Company



**Approved by** M. Ohno  
Manager  
Engineering Department  
Power & Telecommunication Cable Division  
Power & Telecommunication System Company

## Fujikura Ltd.

## CONSTRUCTION DATA

Type of cable		F-3PNCT-S
Rated voltage (kV)		0.6/1
Number of core		24 (6 cores x 4 units)
Conductor	Nominal sectional area (mm <sup>2</sup> )	3.5
	No. and dia. of wire (No./mm)	3/0.3 SUS [ 65/0.26 TA
	Approx. dia. of conductor (mm)	2.5
Earth drain wire	No. and dia. of wire (No./pair)	4/1×2×1.25
Thick. of insulation (mm)		1.2
Thick. of semi-conductive compound (mm)		0.4
Colour code	Core	White X 4, Red, Blue
	Cabling element	Black, White, Red, Green
Thick. of inner sheath (mm)		1.5
Approx. thick. of canvas (mm)		0.5
Thick. of sheath (mm)		4.2
Overall dimension (Height X Width)	Standard (mm)	29.1 X 92.4
	Maximum (mm)	30.6 X 97.0
Approx. net weight (kg/km)		4350
Testing voltage (V/1min.)		3000
Max. conductor resistance at 20°C (Ω/km)		6.09
Min. insulation resistance at 20°C (MΩ-km)		500

Note SUS : Stainless steel wire  
TA : Tinned annealed copper wire

